

Claims:

1. An optical testing unit for measuring sensitivity of an optical device under test (DUT) over an operating range of the DUT comprising:
 - an optical transmitter, which transmits an optical test signal that is transmitted to the DUT;
 - an optical receiver, which receives an input signal from the DUT;
 - a graphical user interface, which provides an interface with a user; a memory module, said memory module comprising a sensitivity module; and
 - a controller, selectively coupled to said transmitter, said receiver and said graphical user interface, wherein said controller provides a central control of said transmitter, said receiver and said graphical user interface.
2. An optical testing unit as recited in claim 1, wherein said memory further comprises a calibration module, said calibration module comprising information utilized by said controller during a calibration procedure.
3. An optical testing unit as recited in claim 1, wherein said memory module further comprises a standard success criteria module, said standard success criteria module comprising information utilized by said controller to compare test results to an industry standard.
4. An optical testing unit as recited in claim 1, wherein the unit is disposed

in a housing.

5. An optical test unit as recited in claim 1, further comprising an optical power monitor, which is controlled by said control unit.

6. An optical testing unit as recited in claim 5, further comprising an optical attenuator, which receives said optical test signal and selectively attenuates said test signal prior to providing an attenuated input signal to the DUT.

7. An optical test unit as recited in claim 6, wherein said control unit actively adjusts at least one of: an output power level of said transmitter; and an attenuation level of said attenuator to transmit said test signal at a desired power level as measured by said optical power monitor.

8. An optical test unit as recited in claim 7, wherein said control unit iteratively performs said adjustments.

9. A method of measuring sensitivity of an optical component, the method comprising:

providing an optical testing unit disposed in a housing;

providing a test optical signal as an output signal from said optical testing unit to a device under test (DUT);

receiving an input signal from said DUT at said optical testing unit;

measuring said sensitivity from said input signal; and

providing a control unit within said housing which controls various

components in said optical test unit.

10. A method as recited in claim 9, wherein said test optical signal is from an optical transmitter within said optical testing unit.

11. A method as recited in claim 9, wherein said input signal is received at an optical receiver within said optical testing unit.

12. A method as recited in claim 9, wherein said controller further comprises a memory module.

13. A method as recited in claim 12, wherein said memory module further comprises a sensitivity module.

14. A method as recited in claim 13, wherein said memory module further comprises a test module.

15. A method as recited in claim 13, wherein said memory module further comprises a calibration module.

16. A method as recited in claim 13, wherein said memory module further comprises a standard success criteria module.

17. A method as recited in claim 9, wherein said optical testing unit further comprises a graphical user interface (GUI).

18. A method as recited in claim 17, wherein said GUI is adapted to receive manual inputs to commence and terminate the measuring.

19. A method as recited in claim 15, wherein said sensitivity measuring is affected after an automated calibration procedure is completed.

20. A method of measuring sensitivity of an optical component comprising the steps of:

measuring a power level of an optical output signal of an optical transmitter;

if said power level is not a first predetermined power level, adjusting said optical output signal until said power level is said first predetermined power level;

transmitting said optical output signal at said first predetermined power level to an optical device under test (DUT);

receiving an optical input signal from said DUT;

calculating a bit error rate of said optical input signal;

comparing said bit error rate with a predetermined bit error rate;

if said bit error rate is equal to said predetermined bit error rate, setting a sensitivity value;

if said bit error rate is not equal to said predetermined bit error rate, changing said first predetermined power level to a second predetermined power level and repeating at least said adjusting step, said transmitting step, said receiving step, said calculating step, and said comparing step.

21. A method as in claim 20, wherein said adjusting step comprises attenuating said optical output signal.

22. A method as in claim 20, wherein said adjusting step comprises adjusting said optical transmitter.

23. A method as in claim 20, wherein said method is automated.